

World Components Network Service Ltd**Customer Name:****Date:**

2017-3-23

Part No:

WCN2S-1040WW-A2

**Product Group
Description:**

LED Display

Customer Part No:**Approval Date:****Customer
Confirmation****Approved by****Checked by**Athena
2017-3-23**Prepared By**Fei
2017-3-23

Country of Origin: China

World Components Network Service Ltd5th Floor,Block A-2,Xuxingda Ind Zone
Shiyan Town,Bao An District , Shenzhen
Tel : (86)755-29000022
Fax : (86)755-29000023[www . wcnopto.net](http://www.wcnopto.net)

Table of Contents

NO.	ITEM	PAGE
1	Cover	1
2	Table of Contents	2
3	Revision Record	3
4	Description	4
5	Outer Dimension and Circuit Diagram	5
6	Absolute Maximum Rating and Electrical/Optical Characteristics Rating	6
7	Typical Electrical/ Optical Characteristic Curves and Spectrometer	7
8	Packaging Data	8
9	Moisture Proof Packaging	9

World Components Network Service Ltd

REVISION RECORD

MARKER	Matter for revision	SHEET	DTAE	MAKER	APPOVED SIGN	
	Reason for revision					
A0	P# WCN2S-1040WW-A2	Whole Spec	2017-3-23	Fei	Athena	
	New Version issued					

1. Type No./Manufacture's Name


WCN2S-1040WW-A2 / World Components Network Service Ltd.

2. Features:

- **High Reliability**
- **Low Power Requirement**
- **Easy Assembly**

3. Faction: Display Digit Characteristic**4. Soldering Conditions: Soldering Temp. 260 ± 5 °C, Soldering Time. 3~5 sec.**

Soldering Power <30 W.

5. Re-flow Temp/Time**NOTES:**


5.1. We recommend the re-flow temperature $245^{\circ}\text{C} (\pm 5^{\circ}\text{C})$. the maximum soldering temperature should be limited to 260°C .

5.2. Don't cause stress to the epoxy resin while it is exposed to high temperature. Number of re-flow process shall be 2 times or less.

6. Description:


- **Two Digit LED Display**
- **Digit Height: 10.16mm (0.4")**
- **Gray Face and Milky Segment**
- **Color: White**

Outer Dimension:



Notes: Unless otherwise stated, the tolerance is $\pm 0.25\text{mm}$.

Circuit Diagram:



Pin Connection:

PIN NO.	CONNECTION	PIN NO.	CONNECTION	PIN NO.	CONNECTION
1	Cathode E1	8	Common Anode dig2	15	Cathode G2
2	Cathode D1	9	Cathode C2	16	Cathode B1
3	Common Anode dig1	10	Cathode dp2	17	Cathode A1
4	Cathode C1	11	Cathode B2	18	Common Anode dig1
5	Cathode DP1	12	Cathode A2	19	Cathode F1
6	Cathode E2	13	Common Anode dig2	20	Cathode G1
7	Cathode D2	14	Cathode F2	/	/

World Components Network Service Ltd

■ ABSOLUTE MAXIMUM RATINGS AT TA=25°C

Parameter	Symbol	Condition	Color	Rating	Units
Power Dissipation Per Chip	P_d	—	White	65	mW
Forward Current Per Chip	I_F	—	White	25	mA
Peak Forward Current Per Chip	I_{FP}	1/10 Duty 1KHz	White	100	mA
Reverse Voltage Per Chip	V_R	—	White	5	V
Operating Temperature Range	T_{opr}	—	—	-40~+105	°C
Storage Temperature Range	T_{stg}	—	—	-40~+105	°C

■ Electrical/Optical Characteristics Rating(Ta=25°C)

Item	Symbol	Test conditions	Location	Rating			Units
				Min.	Typ.	Max.	
Forward Voltage	V_F	$I_F=20mA$	Per Chip	—	3.0	3.6	V
Reverse Current	I_R	$V_R=5V$	Per Chip	—	—	100	μA
Luminous Intensity	I_v	$I_F=10mA$	Per Chip	650	—	950	mcd
CIE Coordinate	X	$I_F=20mA$	Per Chip	—	0.264	—	
	Y			—	0.260	—	
Luminous Intensity Matching Ratio (Segment To Segment)	I_{v-m}	$I_F=10mA$				1.2:1	


■ Luminous Intensity Sorting: (Luminous intensity tolerance :+/-10%)

Rank	Symbol	Condition	Min	Max	Unit
K	K	$I_F=10mA$	650	700	mcd
L	L	$I_F=10mA$	700	750	mcd
M	M	$I_F=10mA$	750	800	mcd
N	N	$I_F=10mA$	800	850	mcd
O	O	$I_F=10mA$	850	900	mcd
P	P	$I_F=10mA$	900	950	mcd


■ **Typical Elector-Optical Characteristics Curve:**

Spectral Distribution


Relative Intensity vs. Wavelength (Ta=25° C)



Forward Current vs. Forward Voltage (Ta=25° C)




Relative Intensity vs. Forward Current (Ta=25° C)




Derating


Relative Intensity vs. Ambient Temperature




Maximum Forward Current vs. Ambient Temperature




Forward Current vs. Chromaticity (Ta=25° C)



■ Packing Reel Dimensions(mm):




■ Dimensions of Tape (Unit: mm)




■ One Reel contained 600 PCS products:

■ Recommended Soldering Pattern:



■ **Moisture Proof Packaging:**

All N/D SMD displays are shipped in moisture proof package. The displays should be stored at 30°C or less and 60% RH or less. Once the package opened, moisture absorption begins.



■ **Baking Conditions:**

If the parts not stored in dry conditions, they must be baked before re-flow to prevent damage to the parts.

Package	Temperature	Time
In Reel	60 °C	≥ 48hours
In Bulk	100 °C	≥ 4hours
	125 °C	≥ 2hours

■ **Baking should only be done once.**