



WCN-03L4RGB-140-WE**SPECIFICATION**

WCN			CUSTOMER Confirmed
Prepared by	Checked by	Approved by	
LiuGuo 2020-3-27	ZhangChun 2020-3-27		



Description

- ◆ Viewing angle:140 deg
- ◆ The materials of the LED dice is AlGaN/P/InGaN/InGaN
- ◆ 5.0mm×4.0mm×1.85mm
- ◆ RoHS compliant lead-free soldering compatible

Package Outline**NOTES:**

1. All dimensions units are millimeters ;
2. All dimensions tolerances are $\pm 0.2\text{mm}$ unless otherwise noted.

Absolute Maximum Ratings at Ta=25°C







Parameter	Symbol	Rating			Units
		R	G	B	
Power Dissipation	Pd	770	1190	1190	mW
Forward current	IF		350		mA
Peak Forward Current	IFP		500		mA
Reverse voltage	VR		5		V
Electrostatic Discharge	ESD		1000		V
Operating temperature	Topr		-30~+85		°C
Storage temperature	Tstg		-40 ~+100		°C
junction temperature	Tj		95		°C



Electrical/Optical characteristics at Ta=25°C

Item	test condition	Symbol	Value			Unit	
			Min.	Typ.	Max.		
Forward voltage	If=350mA	Vf	R	1.8	--	2.2	V
			G	2.8	--	3.4	V
			B	2.8	--	3.4	V
Luminous intensity	If=350mA	Iv	R	30	--	50	LM
			G	60	--	80	LM
			B	15	--	25	LM
Dominant wavelength	If=350mA	λ_d	R	620	--	625	nm
			G	520	--	525	nm
			B	465	--	470	nm
Viewing angle at 50% Iv	If=350mA	2θ1/2	--	140	--	Deg	
Reverse current	Vr=5V	Ir	--	--	10	µA	
Thermal resistance	If=350mA	Rth(j-s)	--	--	450	°C/W	

NOTE:

- 1.1/10 Duty cycle, 0.1ms pulse width.
2. The above forward voltage measurement allowance tolerance is 0.1V.
3. the above luminous intensity measurement allowance tolerance ±10%.

Optical characteristics curves**Forward Current VS Forward Voltage****Relative Flux VS Forward Current****Relative Flux VS Ambient Temperature****Forward Current VS Ambient Temperature****Relative Spectral Distribution****Typical Spectral Distribution**

Packaging Specifications**■ Carrier Tape Dimensions****■ Reel Dimension****NOTE:**

1. The tolerances unless mentioned ±0.1mm. Unit : mm
2. 500 pcs/Reel.

■ Label Form Specification

WCN Opto Group Co., Ltd

P/N:



ROHS

QTY: PCS



IV:

WL:

VF:


LOT NO:



MADE IN CHINA

P/N	Part Number
QTY	Packing Quantity
LOT NO	Made Date
IV	Luminous intensity
WL	Dominant wavelength
VF	Forward Voltage

■ Moisture Resistant Packing Process




Test items and results of reliability

Type	Test Item	Test Conditions	Note	Number of Damaged
Environmental Sequence	Reflow	T _a =260°C max T=10s	2 times	0/22
	Temperature Cycle	-40°C 30min ↑ 100°C 30min	100 cycle	0/22
	Thermal Shock	-40°C 15min ↑ 100°C 15min	100 cycle	0/22
	High Humidity Heat Cycle	30°C ⇄ 65°C 90%RH 24hrs/1cycle	10 cycle	0/22
	High Temperature Storage	T _a =100°C	1000 hrs	0/22
	Low Temperature Storage	T _a =-40°C	1000 hrs	0/22
	Humidity Heat Storage	T _a =60°C RH=90%	1000 hrs	0/22
	Low Temperature Storage	T _a =-30°C	1000 hrs	0/22
Operation Sequence	Life Test	T _a =25°C IF=20mA	1000 hrs	0/22
	High Humidity Heat Life Test	60°C RH=90% IF=10mA	500 hrs	0/22
	Low Temperature Life Test	T _a =-20°C IF=20mA	1000 hrs	0/22

Reflow Profile

■ Reflow Temp/Time



Notes:


1. We recommend the reflow temperature 245°C ($\pm 5^\circ\text{C}$). the maximum soldering temperature should be limited to 260°C.
2. Don't cause stress to the epoxy resin while it is exposed to high temperature.
3. Number of reflow process shall be 2 times or less.

■ Soldering iron

Basic spec is ≤ 5 sec when 260°C. If temperature is higher, time should be shorter ($+10^\circ\text{C} \rightarrow -1$ sec). Power dissipation of iron should be smaller than 20W, and temperatures should be controllable .Surface temperature of the device should be under 230°C .

■ Rework


1. Customer must finish rework within 5 sec under 260°C.
2. The head of iron can not touch copper foil
3. Twin-head type is preferred.



- Avoid rubbing or scraping the resin by any object, during high temperature, for example reflow solder etc.

Test circuit and handling precautions

■ Test circuit



■ Handling precautions

1. Over-current-proof

Customer must apply resistors for protection; otherwise slight voltage shift will cause big current change (Burn out will happen).

2. Storage

2.1 It is recommended to store the products in the following conditions:

Humidity: 60% R.H. Max.

Temperature : 5°C~30°C(41°F~86°F)

2.2 Shelf life in sealed bag: 12 month at <5°C~30°C and <30% R.H. After the package is

Opened, the products should be used within a week or they should be keeping to stored at ≤ 20 R.H. with zip-lock sealed.

3. Baking

It is recommended to baking before soldering when the pack is unsealed after 72hrs. The Conditions are as

followings:

3.1 $70\pm3^\circ\text{C}$ x(12~24hrs) and <5%RH, taped reel type

3.2 $100\pm3^\circ\text{C}$ x(45min~1hr), bulk type

3.3 $130\pm3^\circ\text{C}$ x(15~30min), bulk type